



# ISOPROPYL ACETATE, 98%

## GFS CHEMICALS INC

Version No: 3.2

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 29/01/2025

Print Date: 29/01/2025

S.GHS.USA.EN

### SECTION 1 Identification

#### Product Identifier

|                               |                        |
|-------------------------------|------------------------|
| Product name                  | ISOPROPYL ACETATE, 98% |
| Synonyms                      | Not Available          |
| Proper shipping name          | Isopropyl acetate      |
| Chemical formula              | H3C-COOCH(CH3)2        |
| Other means of identification | Not Available          |
| CAS number                    | 108-21-4               |

#### Recommended use of the chemical and restrictions on use

|                          |   |
|--------------------------|---|
| Relevant identified uses | professional, scientific and technical activities other professional, scientific and technical activities |
|--------------------------|---|

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

|                         |  |
|-------------------------|--|
| Registered company name | GFS CHEMICALS INC  |
| Address                 | 155 Hidden Ravines Dr., Powell OH 43065 Columbus OH United States      |
| Telephone               | +1 740-881-550   |
| Fax                     | Not Available  |
| Website                 | <a href="http://www.gfschemicals.com">www.gfschemicals.com</a>         |
| Email                   | <a href="mailto:service@gfschemicals.com">service@gfschemicals.com</a> |

#### Emergency phone number

|                                     |               |
|-------------------------------------|---------------|
| Association / Organisation          | Chemtrec      |
| Emergency telephone number(s)       | (800)262-8200 |
| Other emergency telephone number(s) | Not Available |

### SECTION 2 Hazard(s) identification

#### Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

|                |   |
|----------------|---|
| Classification | Flammable Liquids Category 2, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3 |
|----------------|---|

#### Label elements

|                     |        |
|---------------------|--------|
| Hazard pictogram(s) |        |
| Signal word         | Danger |

#### Hazard statement(s)

ISOPROPYL ACETATE, 98%

|      |                                     |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H315 | Causes skin irritation.             |
| H319 | Causes serious eye irritation.      |
| H335 | May cause respiratory irritation.   |
| H336 | May cause drowsiness or dizziness.  |

Hazard(s) not otherwise classified

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Precautionary statement(s) Prevention

|      |  |
|------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P233 | Keep container tightly closed.   |
| P271 | Use only outdoors or in a well-ventilated area.  |
| P240 | Ground/bond container and receiving equipment.   |
| P241 | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.              |
| P242 | Use only non-sparking tools.   |
| P243 | Take precautionary measures against static discharge.  |
| P261 | Avoid breathing mist/vapours/spray.  |
| P264 | Wash all exposed external body areas thoroughly after handling.                                |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection.               |

Precautionary statement(s) Response

|                |  |
|----------------|--|
| P370+P378      | In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.  |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312           | Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.  |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P302+P352      | IF ON SKIN: Wash with plenty of water.   |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.                              |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |
| P362+P364      | Take off contaminated clothing and wash it before reuse.   |

Precautionary statement(s) Storage

|           |  |
|-----------|--|
| P403+P235 | Store in a well-ventilated place. Keep cool.                     |
| P405      | Store locked up.   |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

Precautionary statement(s) Disposal

|      |  |
|------|--|
| P501 | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|------|--|

SECTION 3 Composition / information on ingredients

Substances

| CAS No   | %[weight] | Name              |
|----------|-----------|-------------------|
| 108-21-4 | 100       | isopropyl acetate |

Mixtures

See section above for composition of Substances

SECTION 4 First-aid measures

Description of first aid measures

|              |  |
|--------------|--|
| Eye Contact  | <p>If this product comes in contact with eyes:</p> <ul style="list-style-type: none"><li>▶ Wash out immediately with water.</li><li>▶ If irritation continues, seek medical attention.</li><li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li></ul>   |
| Skin Contact | <p>If skin contact occurs:</p> <ul style="list-style-type: none"><li>▶ Immediately remove all contaminated clothing, including footwear.</li><li>▶ Flush skin and hair with running water (and soap if available).</li><li>▶ Seek medical attention in event of irritation.</li></ul>  |
| Inhalation   | <ul style="list-style-type: none"><li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li><li>▶ Lay patient down. Keep warm and rested.</li><li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li><li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li><li>▶ Transport to hospital, or doctor, without delay.</li></ul> |
| Ingestion    | <ul style="list-style-type: none"><li>▶ Immediately give a glass of water.</li><li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li></ul>   |

- 
- ▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

**Most important symptoms and effects, both acute and delayed**  
See Section 11

**Indication of any immediate medical attention and special treatment needed**  
Treat symptomatically.  
Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.  
for simple esters:

BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for pulmonary oedema .
- ▶ Monitor and treat, where necessary, for shock.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- ▶ Give activated charcoal.

ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- ▶ Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Fire-fighting measures

Extinguishing media

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

- Fire Incompatibility
- ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

|               |  |
|---------------|--|
| Fire Fighting | <div>▶ Alert Fire Brigade and tell them location and nature of hazard.</div> <div>▶ May be violently or explosively reactive.</div> <div>▶ Wear breathing apparatus plus protective gloves in the event of a fire.</div> <div>▶ Prevent, by any means available, spillage from entering drains or water course.</div> <div>▶ Consider evacuation (or protect in place).</div> <div>▶ Fight fire from a safe distance, with adequate cover.</div> <div>▶ If safe, switch off electrical equipment until vapour fire hazard removed.</div> <div>▶ Use water delivered as a fine spray to control the fire and cool adjacent area.</div> <div>▶ Avoid spraying water onto liquid pools.</div> <div>▶ <b>Do not approach containers suspected to be hot.</b></div> <div>▶ Cool fire exposed containers with water spray from a protected location.</div> <div>▶ If safe to do so, remove containers from path of fire.</div> |
|---------------|--|

SECTION 6 Accidental release measures

**Personal precautions, protective equipment and emergency procedures**  
See section 8

**Environmental precautions**  
See section 12

## ISOPROPYL ACETATE, 98%

## Methods and material for containment and cleaning up

|              |  |
|--------------|--|
| Minor Spills | <ul style="list-style-type: none"> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb small quantities with vermiculite or other absorbent material.</li> <li>Wipe up.</li> <li>Collect residues in a flammable waste container.</li> </ul>  |
| Major Spills | <ul style="list-style-type: none"> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>May be violently or explosively reactive.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> <li>Consider evacuation (or protect in place).</li> <li>No smoking, naked lights or ignition sources.</li> <li>Increase ventilation.</li> <li>Stop leak if safe to do so.</li> <li>Water spray or fog may be used to disperse /absorb vapour.</li> <li>Contain spill with sand, earth or vermiculite.</li> <li>Use only spark-free shovels and explosion proof equipment.</li> <li>Collect recoverable product into labelled containers for recycling.</li> <li>Absorb remaining product with sand, earth or vermiculite.</li> <li>Collect solid residues and seal in labelled drums for disposal.</li> <li>Wash area and prevent runoff into drains.</li> <li>If contamination of drains or waterways occurs, advise emergency services.</li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

## Precautions for safe handling

|                   |  |
|-------------------|--|
| Safe handling     | <ul style="list-style-type: none"> <li>Containers, even those that have been emptied, may contain explosive vapours.</li> <li>Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> <li><b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>Avoid smoking, naked lights, heat or ignition sources.</li> <li>When handling, <b>DO NOT eat, drink or smoke.</b></li> <li>Vapour may ignite on pumping or pouring due to static electricity.</li> <li><b>DO NOT use plastic buckets.</b></li> <li>Earth and secure metal containers when dispensing or pouring product.</li> <li>Use spark-free tools when handling.</li> <li>Avoid contact with incompatible materials.</li> <li>Keep containers securely sealed.</li> <li>Avoid physical damage to containers.</li> <li>Always wash hands with soap and water after handling.</li> <li>Work clothes should be laundered separately.</li> <li>Use good occupational work practice.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.</li> <li><b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> </ul>  |
| Other information | <ul style="list-style-type: none"> <li>Store in original containers in approved flame-proof area.</li> <li>No smoking, naked lights, heat or ignition sources.</li> <li><b>DO NOT store in pits, depression, basement or areas where vapours may be trapped.</b></li> <li>Keep containers securely sealed.</li> <li>Store away from incompatible materials in a cool, dry well ventilated area.</li> <li>Protect containers against physical damage and check regularly for leaks.</li> <li>Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>Tank storage: Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.</li> <li>Keep in a cool place. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.</li> <li>For containers, or container linings use mild steel, stainless steel. Examples of suitable materials are: high density polyethylene (HDPE), polypropylene (PP), and Viton (FMK), which have been specifically tested for compatibility with this product.</li> <li>For container linings, use amine-adduct cured epoxy paint.</li> <li>For seals and gaskets use: graphite, PTFE, Viton A, Viton B.</li> <li>Unsuitable material: Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Examples of materials to avoid are: natural rubber (NR), nitrile rubber (NBR), ethylene propylene rubber (EPDM), polymethyl methacrylate (PMMA), polystyrene, polyvinyl chloride (PVC), polyisobutylene. However, some may be suitable for glove materials.</li> <li>Do not cut, drill, grind, weld or perform similar operations on or near containers. Containers, even those that have been emptied, can contain explosive vapours.</li> </ul> |

## Conditions for safe storage, including any incompatibilities

|                    |   |
|--------------------|---|
| Suitable container | <ul style="list-style-type: none"> <li>Glass container is suitable for laboratory quantities</li> <li>Packing as supplied by manufacturer.</li> <li>Plastic containers may only be used if approved for flammable liquid.</li> <li>Check that containers are clearly labelled and free from leaks.</li> <li>For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> <li>For materials with a viscosity of at least 2680 cSt. (23 deg. C)</li> <li>For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)</li> <li>Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.</li> </ul> |
|--------------------|---|

Continued...

ISOPROPYL ACETATE, 98%

|                         |   |
|-------------------------|---|
|                         | <div><div>► Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages</div><div>► In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.</div></div>   |
| Storage incompatibility | <div><div>► Esters react with acids to liberate heat along with alcohols and acids.</div><div>► Strong oxidising acids may cause a vigorous reaction with esters that is sufficiently exothermic to ignite the reaction products.</div><div>► Heat is also generated by the interaction of esters with caustic solutions.</div><div>► Flammable hydrogen is generated by mixing esters with alkali metals and hydrides.</div><div>► Esters may be incompatible with aliphatic amines and nitrates.</div><div>► Avoid strong acids, bases.</div></div> |

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source   | Ingredient        | Material name     | TWA                 | STEL          | Peak          | Notes          |
|--|-------------------|-------------------|---------------------|---------------|---------------|----------------|
| US OSHA Permissible Exposure Limits (PELs) Table Z-1 | isopropyl acetate | Isopropyl acetate | 250 ppm / 950 mg/m3 | Not Available | Not Available | Not Available  |
| US NIOSH Recommended Exposure Limits (RELs)          | isopropyl acetate | Isopropyl acetate | Not Available       | Not Available | Not Available | See Appendix D |

Emergency Limits

| Ingredient        | TEEL-1  | TEEL-2    | TEEL-3      |
|-------------------|---------|-----------|-------------|
| isopropyl acetate | 200 ppm | 2700* ppm | 16000** ppm |

| Ingredient        | Original IDLH | Revised IDLH  |
|-------------------|---------------|---------------|
| isopropyl acetate | 1,800 ppm     | Not Available |

Exposure controls

|   | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.</p> <p>Air contaminants generated in the workplace possess varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to effectively remove the contaminant.</p>   |                        |                        |  |                                 |   |                                  |  |                               |   |                                  |
|---|---|------------------------|------------------------|--|---------------------------------|---|----------------------------------|--|-------------------------------|---|----------------------------------|
|   | <table><tr><th>Type of Contaminant:</th><th>Air Speed:</th></tr><tr><td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td><td>0.25-0.5 m/s (50-100 f/min.)</td></tr><tr><td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td><td>0.5-1 m/s (100-200 f/min.)</td></tr><tr><td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td><td>1-2.5 m/s (200-500 f/min.)</td></tr></table>  | Type of Contaminant:   | Air Speed:             | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s (50-100 f/min.)    | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)       | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.)    |   |                                  |
| Type of Contaminant:  | Air Speed:  |                        |                        |  |                                 |   |                                  |  |                               |   |                                  |
| solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s (50-100 f/min.)  |                        |                        |  |                                 |   |                                  |  |                               |   |                                  |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)  |                        |                        |  |                                 |   |                                  |  |                               |   |                                  |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s (200-500 f/min.)  |                        |                        |  |                                 |   |                                  |  |                               |   |                                  |
| Appropriate engineering controls  | <p>Within each range the appropriate value depends on:</p> <table><tr><th>Lower end of the range</th><th>Upper end of the range</th></tr><tr><td>1: Room air currents minimal or favourable to capture</td><td>1: Disturbing room air currents</td></tr><tr><td>2: Contaminants of low toxicity or of nuisance value only.</td><td>2: Contaminants of high toxicity</td></tr><tr><td>3: Intermittent, low production.</td><td>3: High production, heavy use</td></tr><tr><td>4: Large hood or large air mass in motion</td><td>4: Small hood-local control only</td></tr></table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> <p>· Adequate ventilation is typically taken to be that which limits the average concentration to no more than 25% of the LEL within the building, room or enclosure containing the dangerous substance.</p> <p>· Ventilation for plant and machinery is normally considered adequate if it limits the average concentration of any dangerous substance that might potentially be present to no more than 25% of the LEL. However, an increase up to a maximum 50% LEL can be acceptable where additional safeguards are provided to prevent the formation of a hazardous explosive atmosphere. For example, gas detectors linked to emergency shutdown of the process might be used together with maintaining or increasing the exhaust ventilation on solvent evaporating ovens and gas turbine enclosures.</p> <p>· Temporary exhaust ventilation systems may be provided for non-routine higher-risk activities, such as cleaning, repair or maintenance in tanks or other confined spaces or in an emergency after a release. The work procedures for such activities should be carefully considered..</p> <p>The atmosphere should be continuously monitored to ensure that ventilation is adequate and the area remains safe. Where workers will enter the space, the ventilation should ensure that the concentration of the dangerous substance does not exceed 10% of the LEL (irrespective of the provision of suitable breathing apparatus)</p> | Lower end of the range | Upper end of the range | 1: Room air currents minimal or favourable to capture                    | 1: Disturbing room air currents | 2: Contaminants of low toxicity or of nuisance value only.  | 2: Contaminants of high toxicity | 3: Intermittent, low production.   | 3: High production, heavy use | 4: Large hood or large air mass in motion | 4: Small hood-local control only |
| Lower end of the range  | Upper end of the range  |                        |                        |  |                                 |   |                                  |  |                               |   |                                  |
| 1: Room air currents minimal or favourable to capture   | 1: Disturbing room air currents   |                        |                        |  |                                 |   |                                  |  |                               |   |                                  |
| 2: Contaminants of low toxicity or of nuisance value only.  | 2: Contaminants of high toxicity  |                        |                        |  |                                 |   |                                  |  |                               |   |                                  |
| 3: Intermittent, low production.  | 3: High production, heavy use   |                        |                        |  |                                 |   |                                  |  |                               |   |                                  |
| 4: Large hood or large air mass in motion   | 4: Small hood-local control only  |                        |                        |  |                                 |   |                                  |  |                               |   |                                  |

## ISOPROPYL ACETATE, 98%

|   |   |
|---|---|
| Individual protection measures, such as personal protective equipment |    |
| Eye and face protection   | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].</li> </ul>  |
| Skin protection   | See Hand protection below   |
| Hands/feet protection   | <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p>For esters:</p> <ul style="list-style-type: none"> <li>▶ Do NOT use natural rubber, butyl rubber, EPDM or polystyrene-containing materials.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>· frequency and duration of contact,</li> <li>· chemical resistance of glove material,</li> <li>· glove thickness and</li> <li>· dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>· Contaminated gloves should be replaced.</li> </ul> <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>· Excellent when breakthrough time &gt; 480 min</li> <li>· Good when breakthrough time &gt; 20 min</li> <li>· Fair when breakthrough time &lt; 20 min</li> <li>· Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> |
| Body protection   | See Other protection below  |
| Other protection  | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ PVC Apron.</li> <li>▶ PVC protective suit may be required if exposure severe.</li> <li>▶ Eyewash unit.</li> <li>▶ Ensure there is ready access to a safety shower.</li> <li>▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</li> <li>▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</li> <li>▶ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.</li> </ul>   |

## Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the 'Exposure Standard' (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES                      | Air-line*            | A-2                  | A-PAPR-2 ^             |
| up to 20 x ES                      | -                    | A-3                  | -                      |
| 20+ x ES                           | -                    | Air-line**           | -                      |

\* - Continuous-flow; \*\* - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.

Continued...

## ISOPROPYL ACETATE, 98%

- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## SECTION 9 Physical and chemical properties

## Information on basic physical and chemical properties

|   |                          |  |  |
|---|--------------------------|--|--|
| <b>Appearance</b>                                     | Clear.                   |  |  |
| <b>Physical state</b>                                 | Liquid                   | <b>Relative density (Water = 1)</b>                        | 0.87   |
| <b>Odour</b>  | Not Available            | <b>Partition coefficient n-octanol / water</b>             | Not Available  |
| <b>Odour threshold</b>                                | Not Available            | <b>Auto-ignition temperature (°C)</b>                      | 460  |
| <b>pH (as supplied)</b>                               | Not Available            | <b>Decomposition temperature (°C)</b>                      | Not Available  |
| <b>Melting point / freezing point (°C)</b>            | -73.4                    | <b>Viscosity (cSt)</b>                                     | viscosity 0.49 mPa.s (77 °F (25 °C))Kinematic viscosity 0.5621 mm²/s estimated |
| <b>Initial boiling point and boiling range (°C)</b>   | 88.6                     | <b>Molecular weight (g/mol)</b>                            | 102.13 g/mol   |
| <b>Flash point (°C)</b>                               | 2.0                      | <b>Taste</b>   | Not Available  |
| <b>Evaporation rate</b>                               | Not Available            | <b>Explosive properties</b>                                | Not Available  |
| <b>Flammability</b>                                   | HIGHLY FLAMMABLE.        | <b>Oxidising properties</b>                                | Not Available  |
| <b>Upper Explosive Limit (%)</b>                      | Not Available            | <b>Surface Tension (dyn/cm or mN/m)</b>                    | Not Available  |
| <b>Lower Explosive Limit (%)</b>                      | Not Available            | <b>Volatile Component (%vol)</b>                           | 100 %  |
| <b>Vapour pressure (kPa)</b>                          | 8.05 kPa (77 °F (25 °C)) | <b>Gas group</b>   | Not Available  |
| <b>Solubility in water</b>                            | Miscible                 | <b>pH as a solution (1%)</b>                               | Not Available  |
| <b>Vapour density (Air = 1)</b>                       | 3.52                     | <b>VOC g/L</b>   | 100 %  |
| <b>Heat of Combustion (kJ/g)</b>                      | Not Available            | <b>Ignition Distance (cm)</b>                              | Not Available  |
| <b>Flame Height (cm)</b>                              | Not Available            | <b>Flame Duration (s)</b>                                  | Not Available  |
| <b>Enclosed Space Ignition Time Equivalent (s/m3)</b> | Not Available            | <b>Enclosed Space Ignition Deflagration Density (g/m3)</b> | Not Available  |
| <b>Nanoform Solubility</b>                            | Not Available            | <b>Nanoform Particle Characteristics</b>                   | Not Available  |
| <b>Particle Size</b>                                  | Not Available            |  |  |

## SECTION 10 Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

## SECTION 11 Toxicological information

## Information on toxicological effects

|   |  |
|---|--|
| <b>a) Acute Toxicity</b>                    | Based on available data, the classification criteria are not met.  |
| <b>b) Skin Irritation/Corrosion</b>         | There is sufficient evidence to classify this material as skin corrosive or irritating.                    |
| <b>c) Serious Eye Damage/Irritation</b>     | There is sufficient evidence to classify this material as eye damaging or irritating                       |
| <b>d) Respiratory or Skin sensitisation</b> | Based on available data, the classification criteria are not met.  |
| <b>e) Mutagenicity</b>                      | Based on available data, the classification criteria are not met.  |
| <b>f) Carcinogenicity</b>                   | Based on available data, the classification criteria are not met.  |
| <b>g) Reproductivity</b>                    | Based on available data, the classification criteria are not met.  |
| <b>h) STOT - Single Exposure</b>            | There is sufficient evidence to classify this material as toxic to specific organs through single exposure |
| <b>i) STOT - Repeated Exposure</b>          | Based on available data, the classification criteria are not met.  |
| <b>j) Aspiration Hazard</b>                 | Based on available data, the classification criteria are not met.  |

|                |  |
|----------------|--|
| <b>Inhaled</b> | Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. |
|----------------|--|



## ISOPROPYL ACETATE, 98%

|   | The main effects of simple esters are irritation, stupor and insensibility. Headache, drowsiness, dizziness, coma and behavioural changes may occur.<br>Inhalation hazard is increased at higher temperatures.  |          |            |   |                         |   |  |  |   |  |  |  |  |
|---|---|----------|------------|---|-------------------------|---|--|--|---|--|--|--|--|
| <b>Ingestion</b>                                  | The material is not thought to produce adverse health effects following ingestion (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum.  |          |            |   |                         |   |  |  |   |  |  |  |  |
| <b>Skin Contact</b>                               | The material may accentuate any pre-existing dermatitis condition<br>Open cuts, abraded or irritated skin should not be exposed to this material<br>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.<br>The material may cause mild but significant inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering. |          |            |   |                         |   |  |  |   |  |  |  |  |
| <b>Eye</b>  | Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).  |          |            |   |                         |   |  |  |   |  |  |  |  |
| <b>Chronic</b>                                    | Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.<br>Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS]   |          |            |   |                         |   |  |  |   |  |  |  |  |
| <b>ISOPROPYL ACETATE, 98%</b>                     | <table border="1"> <thead> <tr> <th>TOXICITY</th><th>IRRITATION</th></tr> </thead> <tbody> <tr> <td>Dermal (rabbit) LD50: &gt;20000 mg/kg<sup>[2]</sup></td><td>Eye (Human): 200ppm/15M</td></tr> <tr> <td>Oral (Rabbit) LD50: 6946 mg/kg<sup>[2]</sup></td><td>Eye: adverse effect observed (irritating)<sup>[1]</sup></td></tr> <tr> <td></td><td>Eye: no adverse effect observed (not irritating)<sup>[1]</sup></td></tr> <tr> <td></td><td>Skin (Rodent - rabbit): 500mg/24H - Mild</td></tr> <tr> <td></td><td>Skin: no adverse effect observed (not irritating)<sup>[1]</sup></td></tr> </tbody> </table>                                     | TOXICITY | IRRITATION | Dermal (rabbit) LD50: >20000 mg/kg <sup>[2]</sup> | Eye (Human): 200ppm/15M | Oral (Rabbit) LD50: 6946 mg/kg <sup>[2]</sup> | Eye: adverse effect observed (irritating) <sup>[1]</sup> |  | Eye: no adverse effect observed (not irritating) <sup>[1]</sup> |  | Skin (Rodent - rabbit): 500mg/24H - Mild |  | Skin: no adverse effect observed (not irritating) <sup>[1]</sup> |
| TOXICITY  | IRRITATION  |          |            |   |                         |   |  |  |   |  |  |  |  |
| Dermal (rabbit) LD50: >20000 mg/kg <sup>[2]</sup> | Eye (Human): 200ppm/15M   |          |            |   |                         |   |  |  |   |  |  |  |  |
| Oral (Rabbit) LD50: 6946 mg/kg <sup>[2]</sup>     | Eye: adverse effect observed (irritating) <sup>[1]</sup>  |          |            |   |                         |   |  |  |   |  |  |  |  |
|   | Eye: no adverse effect observed (not irritating) <sup>[1]</sup>   |          |            |   |                         |   |  |  |   |  |  |  |  |
|   | Skin (Rodent - rabbit): 500mg/24H - Mild  |          |            |   |                         |   |  |  |   |  |  |  |  |
|   | Skin: no adverse effect observed (not irritating) <sup>[1]</sup>  |          |            |   |                         |   |  |  |   |  |  |  |  |

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|   |  |
|---|--|
| <b>ISOPROPYL ACETATE, 98%</b>                         | <p>Generally, linear and branched-chain alkyl esters are hydrolysed to their component alcohols and carboxylic acids in the intestinal tract, blood and most tissues throughout the body. Following hydrolysis the component alcohols and carboxylic acids are metabolized</p> <p>Oral acute toxicity studies have been reported for 51 of the 67 esters of aliphatic acyclic primary alcohols and aliphatic linear saturated carboxylic acids. The very low oral acute toxicity of this group of esters is demonstrated by oral LD50 values greater than 1850 mg/kg bw</p> <p>Genotoxicity studies have been performed in vitro using the following esters of aliphatic acyclic primary alcohols and aliphatic linear saturated carboxylic acids: methyl acetate, butyl acetate, butyl stearate and the structurally related isoamyl formate and demonstrates that these substances are not genotoxic.</p> <p>The JEFCA Committee concluded that the substances in this group would not present safety concerns at the current levels of intake the esters of aliphatic acyclic primary alcohols and aliphatic linear saturated carboxylic acids are generally used as flavouring substances up to average maximum levels of 200 mg/kg. Higher levels of use (up to 3000 mg/kg) are permitted in food categories such as chewing gum and hard candy. In Europe the upper use levels for these flavouring substances are generally 1 to 30 mg/kg foods and in special food categories like candy and alcoholic beverages up to 300 mg/kg foods</p> <p><b>International Program on Chemical Safety: the Joint FAO/WHO Expert Committee on Food Additives (JECFA)</b><br/> <b>Esters of Aliphatic acyclic primary alcohols with aliphatic linear saturated carboxylic acids.; 1998</b></p> |
| <b>ISOPROPYL ACETATE</b>                              | <p>The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.</p>   |
| <b>ISOPROPYL ACETATE, 98% &amp; ISOPROPYL ACETATE</b> | <p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.</p>   |

|  |   |                                 |   |
|--|---|---------------------------------|---|
| <b>Acute Toxicity</b>                    | ✗ | <b>Carcinogenicity</b>          | ✗ |
| <b>Skin Irritation/Corrosion</b>         | ✓ | <b>Reproductivity</b>           | ✗ |
| <b>Serious Eye Damage/Irritation</b>     | ✓ | <b>STOT - Single Exposure</b>   | ✓ |
| <b>Respiratory or Skin sensitisation</b> | ✗ | <b>STOT - Repeated Exposure</b> | ✗ |
| <b>Mutagenicity</b>                      | ✗ | <b>Aspiration Hazard</b>        | ✗ |

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
 ✓ – Data available to make classification

## SECTION 12 Ecological information

## Toxicity

| ISOPROPYL ACETATE, 98% |           |                    |                               |          |        |
|------------------------|-----------|--------------------|-------------------------------|----------|--------|
|                        | Endpoint  | Test Duration (hr) | Species                       | Value    | Source |
|                        | EC50      | 96h                | Algae or other aquatic plants | 37.1mg/l | 2      |
|                        | EC50      | 72h                | Algae or other aquatic plants | 250mg/l  | 2      |
|                        | EC50(ECx) | 96h                | Algae or other aquatic plants | 37.1mg/l | 2      |
|                        | EC50      | 48h                | Crustacea                     | 110mg/l  | 1      |
|                        | LC50      | 96h                | Fish                          | 400mg/l  | 2      |

Continued...



ISOPROPYL ACETATE, 98%

**Legend:** Extracted from 1. IUCIID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient        | Persistence: Water/Soil | Persistence: Air |
|-------------------|-------------------------|------------------|
| isopropyl acetate | LOW                     | LOW              |

Bioaccumulative potential

| Ingredient        | Bioaccumulation |
|-------------------|-----------------|
| isopropyl acetate | LOW (BCF = 1.8) |

Mobility in soil

| Ingredient        | Mobility              |
|-------------------|-----------------------|
| isopropyl acetate | LOW (Log KOC = 9.479) |

Other adverse effects

No evidence of ozone depleting properties were found in the current literature.


SECTION 13 Disposal considerations

Waste treatment methods

|                              |   |
|------------------------------|---|
| Product / Packaging disposal | <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"><li>▶ Reduction</li><li>▶ Reuse</li><li>▶ Recycling</li><li>▶ Disposal (if all else fails)</li></ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"><li>▶ DO NOT allow wash water from cleaning or process equipment to enter drains.</li><li>▶ It may be necessary to collect all wash water for treatment before disposal.</li><li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li><li>▶ Where in doubt contact the responsible authority.</li><li>▶ Recycle wherever possible.</li><li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li><li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li><li>▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li></ul> |
|------------------------------|---|

SECTION 14 Transport information

Labels Required

|                  |   |
|------------------|---|
|                  |  |
| Marine Pollutant | NO  |

Shipping container, transport vehicle placarding, and labeling may vary from the below information. This depends on the quantity shipped, the applicability of excepted quantity requirements, limited quantity requirements, and/or special provisions according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

Land transport (DOT)

|                                    |  |              |   |                    |                |
|------------------------------------|--|--------------|---|--------------------|----------------|
| 14.1. UN number or ID number       | 1220   |              |   |                    |                |
| 14.2. UN proper shipping name      | Isopropyl acetate  |              |   |                    |                |
| 14.3. Transport hazard class(es)   | <table><tr><td>Class</td><td>3</td></tr><tr><td>Subsidiary Hazard</td><td>Not Applicable</td></tr></table>       | Class        | 3 | Subsidiary Hazard  | Not Applicable |
| Class                              | 3  |              |   |                    |                |
| Subsidiary Hazard                  | Not Applicable   |              |   |                    |                |
| 14.4. Packing group                | II   |              |   |                    |                |
| 14.5. Environmental hazard         | Not Applicable   |              |   |                    |                |
| 14.6. Special precautions for user | <table><tr><td>Hazard Label</td><td>3</td></tr><tr><td>Special provisions</td><td>IB2, T4, TP1</td></tr></table> | Hazard Label | 3 | Special provisions | IB2, T4, TP1   |
| Hazard Label                       | 3  |              |   |                    |                |
| Special provisions                 | IB2, T4, TP1   |              |   |                    |                |

Air transport (ICAO-IATA / DGR)

ISOPROPYL ACETATE, 98%

|                                    |   |                |
|------------------------------------|---|----------------|
| 14.1. UN number                    | 1220  |                |
| 14.2. UN proper shipping name      | Isopropyl acetate   |                |
| 14.3. Transport hazard class(es)   | ICAO/IATA Class   | 3              |
|                                    | ICAO / IATA Subsidiary Hazard                             | Not Applicable |
|                                    | ERG Code  | 3L             |
| 14.4. Packing group                | II  |                |
| 14.5. Environmental hazard         | Not Applicable  |                |
| 14.6. Special precautions for user | Special provisions  | Not Applicable |
|                                    | Cargo Only Packing Instructions                           | 364            |
|                                    | Cargo Only Maximum Qty / Pack                             | 60 L           |
|                                    | Passenger and Cargo Packing Instructions                  | 353            |
|                                    | Passenger and Cargo Maximum Qty / Pack                    | 5 L            |
|                                    | Passenger and Cargo Limited Quantity Packing Instructions | Y341           |
|                                    | Passenger and Cargo Limited Maximum Qty / Pack            | 1 L            |

Sea transport (IMDG-Code / GGVSee)

|                                    |                        |                |
|------------------------------------|------------------------|----------------|
| 14.1. UN number                    | 1220                   |                |
| 14.2. UN proper shipping name      | ISOPROPYL ACETATE      |                |
| 14.3. Transport hazard class(es)   | IMDG Class             | 3              |
|                                    | IMDG Subsidiary Hazard | Not Applicable |
| 14.4. Packing group                | II                     |                |
| 14.5. Environmental hazard         | Not Applicable         |                |
| 14.6. Special precautions for user | EMS Number             | F-E , S-D      |
|                                    | Special provisions     | Not Applicable |
|                                    | Limited Quantities     | 1 L            |

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

| Product name      | Pollution Category | Ship Type |
|-------------------|--------------------|-----------|
| Isopropyl acetate | Z                  | 3         |

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name      | Group         |
|-------------------|---------------|
| isopropyl acetate | Not Available |

14.7.3. Transport in bulk in accordance with the IGC Code

| Product name      | Ship Type     |
|-------------------|---------------|
| isopropyl acetate | Not Available |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

|  |
|--|
| isopropyl acetate is found on the following regulatory lists                             |
| US - Massachusetts - Right To Know Listed Chemicals                                      |
| US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Flammables |
| US - New Jersey Right to Know Hazardous Substances                                       |
| US - Pennsylvania - Hazardous Substance List   |
| US DOE Temporary Emergency Exposure Limits (TEELs)                                       |
| US New York City Community Right-to-Know: List of Hazardous Substances                   |
| US NIOSH Recommended Exposure Limits (RELs)  |
| US OSHA Permissible Exposure Limits (PELs) Table Z-1                                     |
| US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory                    |

Additional Regulatory Information

Not Applicable

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

|   |     |
|---|-----|
| Section 311/312 hazard categories               |     |
| Flammable (Gases, Aerosols, Liquids, or Solids) | Yes |

ISOPROPYL ACETATE, 98%

|  |     |
|--|-----|
| Gas under pressure   | No  |
| Explosive  | No  |
| Self-heating   | No  |
| Pyrophoric (Liquid or Solid)                                 | No  |
| Pyrophoric Gas   | No  |
| Corrosive to metal   | No  |
| Oxidizer (Liquid, Solid or Gas)                              | No  |
| Organic Peroxide   | No  |
| Self-reactive  | No  |
| In contact with water emits flammable gas                    | No  |
| Combustible Dust   | No  |
| Carcinogenicity  | No  |
| Acute toxicity (any route of exposure)                       | No  |
| Reproductive toxicity  | No  |
| Skin Corrosion or Irritation                                 | Yes |
| Respiratory or Skin Sensitization                            | No  |
| Serious eye damage or eye irritation                         | Yes |
| Specific target organ toxicity (single or repeated exposure) | Yes |
| Aspiration Hazard  | No  |
| Germ cell mutagenicity                                       | No  |
| Simple Asphyxiant  | No  |
| Hazards Not Otherwise Classified                             | Yes |

**US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)**  
None Reported

**US. EPCRA Section 313 Toxic Release Inventory (TRI) (40 CFR 372)**  
None Reported

**Additional Federal Regulatory Information**  
Not Applicable

State Regulations

**US. California Proposition 65**  
None Reported

**Additional State Regulatory Information**  
Not Applicable

National Inventory Status

| National Inventory                              | Status  |
|---|---|
| Australia - AIIC / Australia Non-Industrial Use | Yes   |
| Canada - DSL                                    | Yes   |
| Canada - NDSL                                   | No (isopropyl acetate)  |
| China - IECSC                                   | Yes   |
| Europe - EINEC / ELINCS / NLP                   | Yes   |
| Japan - ENCS                                    | Yes   |
| Korea - KECI                                    | Yes   |
| New Zealand - NZIoC                             | Yes   |
| Philippines - PICCS                             | Yes   |
| USA - TSCA                                      | All chemical substances in this product have been designated as TSCA Inventory 'Active'   |
| Taiwan - TCSI                                   | Yes   |
| Mexico - INSQ                                   | Yes   |
| Vietnam - NCI                                   | Yes   |
| Russia - FBEPH                                  | Yes   |
| Legend:   | Yes = All CAS declared ingredients are on the inventory<br>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

SECTION 16 Other information

|               |            |
|---------------|------------|
| Revision Date | 29/01/2025 |
| Initial Date  | 26/10/2022 |

SDS Version Summary

ISOPROPYL ACETATE, 98%

| Version | Date of Update | Sections Updated   |
|---------|----------------|--|
| 1.2     | 28/01/2025     | Toxicological information - Acute Health (inhaled), Toxicological information - Acute Health (skin), Toxicological information - Acute Health (swallowed), Toxicological information - Chronic Health, Hazards identification - Classification, Ecological Information - Environmental, First Aid measures - First Aid (inhaled), First Aid measures - First Aid (skin), Handling and storage - Handling Procedure, Exposure controls / personal protection - Personal Protection (eye), Exposure controls / personal protection - Personal Protection (hands/feet), Identification of the substance / mixture and of the company / undertaking - Supplier Information |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC - TWA: Permissible Concentration-Time Weighted Average
- PC - STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit,
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- IBC: International Bulk Chemical Code
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.