

SAFETY DATA SHEET

Date Issued : 07/28/2021 SDS No : 11348

ISOPROPYL ALCOHOL

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ISOPROPYL ALCOHOL PRODUCT CODE: IPA0674 PRODUCT FORMULATION NAME: ISOPROPYL ALCOHOL 99% USP

SUPPLIER:

KTEC Equipment and Supplies 6935 W. Frye Rd. Chandler, AZ 85226 **Customer Service:** 4808390003

24 HR. EMERGENCY TELEPHONE NUMBERS CHEMTREC (US Transportation) :(800) 424 - 9300

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Eye Irritation, Category 2 Target Organ Toxicity (Single exposure), Category 2

Physical:

Flammable Liquids, Category 2

GHS LABEL



SIGNAL WORD: DANGER

HAZARD STATEMENTS

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

- P240: Ground and bond container and receiving equipment.
- P241: Use explosion-proof [electrical/ventilating/lighting/...] equipment.
- P242: Use non-sparking tools.

ISOPROPYL ALCOHOL

P243: Take action to prevent static discharges. P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: WARNING! Flammable liquid and vapor. Harmful or fatal if swallowed. Vapor harmful. May cause central nervous system depression. May be irritating to eyes and skin.

POTENTIAL HEALTH EFFECTS

EYES: Moderately irritating to eyes.

SKIN: Mildly irritating to the skin.

INGESTION: Irritating to the gastrointestinal tract, causing abdominal pain and vomiting, sometimes bloody. Ingestion may cause CNS depression, low blood pressure, rapid heart beat and liver damage.

INHALATION: May cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression.

MEDICAL CONDITIONS AGGRAVATED: Preexisting diseases in or history of ailments involving skin, central nervous system, liver and kidney.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
IPA	99 - 100	67-63-0

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Flush skin with water while removing contaminated clothing. If irritation occurs, get medical attention. Do not reuse clothing or shoes until cleaned.

INGESTION: Rinse mouth with water. Do not induce vomiting; get medical attention.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

ACUTE EFFECTS: Irritation as noted above. Early to moderate CNS depression may be evidenced by giddiness, headache, dizziness, and nausea; in extreme cases, unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis (bluish skin). Liver damage may be evidenced by loss of appetite, jaundice and sometimes pain in the upper abdomen on the right side.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water fog, "alcohol" foam, dry chemical, or CO2.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

- **EXPLOSION HAZARDS:** When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.
- **FIRE FIGHTING PROCEDURES:** WARNING! Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death. Observe all federal, state, and local regulations and National Fire Protection Association (NFPA) Codes with pertain to the specific local conditions of stage and use, including OSHA 29 CFR 1910.106 and NFPA 30, 70, 77, and 497.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
	EXPOSURE LIMITS				
Chemical Name	Туре		ppm	mg/m ³	
IPA	OSHA PEL	TWA	400	980	
	ACGIH TLV	TWA	200	490	
		STEL	400	960	
	Supplier OEL	TWA	NL [1]	NL [1]	
		STEL	NL	NL	
Footnotes:	•				

1. NL = Not Listed

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

- **EYES AND FACE:** Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.
- **SKIN:** Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.
- **RESPIRATORY:** If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

PROTECTIVE CLOTHING: Where splashing is possible, full chemically resistant protective clothing (e.g., acid

ISOPROPYL ALCOHOL

suit) and boots are required.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid **ODOR:** Mild odor. COLOR: Clear, colorless liquid. **PERCENT VOLATILE:** 100 FLASH POINT AND METHOD: 12°C (53°F) LOWER EXPLOSION LIMIT: 0.02 **UPPER EXPLOSION LIMIT: 0.127 AUTOIGNITION TEMPERATURE:** (750°F) **VAPOR PRESSURE:** 32 VAPOR DENSITY: Heavier than air. **BOILING POINT:** $(180^{\circ}F)$ to $(181^{\circ}F)$ **FREEZING POINT:** NDA = no data available. **MELTING POINT:** (-127°F) **SOLUBILITY IN WATER:** Infinitely soluble **EVAPORATION RATE:** Slower than ether. **DENSITY: 6.545** SPECIFIC GRAVITY: 0.78 to 0.80

(VOC): 6.55 LBS./gal.

10. STABILITY AND REACTIVITY

REACTIVITY: Yes

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Avoid heat, sparks, flame and contact with strong oxidizing agents. Do not store or handle in aluminum equipment at temperatures above 120 deg. F.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion. There should be no decomposition if stored and applied as directed.

INCOMPATIBLE MATERIALS: Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

COMMENTS: None Expected.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Avoid uncontrolled releases of this material. Where spills are possible,

ISOPROPYL ALCOHOL

a comprehensive spill response plan should be developed and implemented.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION) PROPER SHIPPING NAME: Isopropanol PRIMARY HAZARD CLASS/DIVISION: 3 UN/NA NUMBER: UN 1219 PACKING GROUP: II NAERG: 129 LABEL: Flammable liquid

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Liquid

R11: Highly flammable.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HEALTH HAZARDS: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

313 REPORTABLE INGREDIENTS: To the best of our knowledge, this product is not listed as a toxic chemical under Section 313 of SARA Title III.

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
IPA	99 - 100	67-63-0

Page 6 of 6

ISOPROPYL ALCOHOL

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: To the best of our knowledge, this product is not listed as an extremely hazardous substance.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

C	hemical Name	CAS
IP	PA	67-63-0

TSCA STATUS: Listed.

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION




S23: Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

GENERAL COMMENTS: The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

16. OTHER INFORMATION

APPROVED BY: Compliance

Date Prepared: 07/28/2021



NFPA STORAGE CLASSIFICATION: These ratings are part of a specific hazard communication program and should be disregarded where individuals are not trained in the use of this hazard rating system. You should be familiar with the hazard communication programs applicable to your workplace.

HMIS RATINGS NOTES: The HMIS rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in the SDS must be considered.

ADDITIONAL SDS INFORMATION: Last revision 06/13/20012

SUPPLIER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, KTEC EQUIPMENT AND SUPPLIES makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. KTEC assumes no responsibility for injuries from the use of the product described herein.