

Classified According to OSHA Hazard Communication Standard (HCS)

SECTION 1: Identification

1.1. Product Identifier

Trade Name or Designation: Aluminum ICP Standard, 10,000 ppm Al in 5% HCl

Product Number: PAL10KH

Other Identifying Product Numbers: PAL10KH-100, PAL10KH-500

1.2. Recommended Use and Restrictions on Use

General Laboratory Reagent

1.3. Details of the Supplier of the Safety Data Sheet

Company: Ricca Chemical Company Address: 448 West Fork Drive

Arlington, TX 76012 USA

Telephone: 888-467-4222

1.4. Emergency Telephone Number (24 hours)

CHEMTREC (USA) 800-424-9300 CHEMTREC (International) 1+ 703-527-3887

SECTION 2: Hazard(s) Identification

2.1. Classification of the Substance or Mixture

For the full text of the Hazard and Precautionary Statements listed below, see Section 16.

		Hazard	
Hazard Class	Category	Statements:	Precautionary Statements:
Skin Corrosion / Irritation	Category 1	H314	P260, P264, P280, P301+P330+P331,
			P303+P361+P353, P363, P304+P340, P310,
			P321, P305+P351+P338, P405, P501
Eye Damage / Irritation	Category 1	H318	P280, P305+P351+P338, P310
Corrosive to Metals	Category 1	H290	P234, P390, P406

Product Number: PAL10KH Page 1 of 16



2.2. GHS Label Elements

Pictograms:



Signal Word: Danger

Hazard Statements:

Hazard Number	Hazard Statement
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

Precautionary Statements:

Precautionary Number	Precautionary Statement
P234	Keep only in original container.
P260	Do not breathe fumes, mist, vapors, or spray.
P264	Wash arms, hands and face thoroughly after handling.
P280	Wear protective gloves and eye protection.
P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy
	to do. Continue rinsing.
P310	Immediately call a POISON CENTER or physician.
P321	Specific treatment (Wash areas of contact with water.
).
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
P405	Store locked up.
P406	Store in corrosive resistant container with a resistant inner liner.
P501	Dispose of contents in accordance with local, state, federal and international regulations.

2.4. Hazards not Otherwise Classified or Covered by GHS

Data not available.

Product Number: PAL10KH Page 2 of 16

SECTION 3: Composition / Information on Ingredients

3.1. Components of Substance or Mixture

Chemical Name	Formula	Molecular Weight CAS Number	er Weight%
Water	H_2O	18.01 g/mol 7732-18-5	96.88
Hydrochloric Acid	HCI	36.46 g/mol 7647-01-0	2.14
Aluminum	Al	26.98 g/mol 7429-90-5	0.98

SECTION 4: First-Aid Measures

4.1. General First Aid Information

Eye Contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. May cause irritation, redness, pain, and tearing.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Skin Contact: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. May cause irritation, redness, and

pain.

Ingestion: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Dilute with water or milk. Do not induce vomiting. Call a physician if

necessary.

4.2. Most Important Symptoms and Effects, Acute and Delayed

Causes severe skin burns and eye damage. Causes serious eye damage. Mildly corrosive. May irritate eyes and skin. Wash areas of contact with water for at least 15 minutes. If ingested, dilute with water. Do not induce vomiting. Call a physician if necessary. EYE CONTACT: May cause irritation, redness, pain, and tearing. SKIN CONTACT: May cause irritation, redness, and pain.

4.3. Medical Attention or Special Treatment Needed

Immediately call a POISON CENTER or physician. Specific treatment (Wash areas of contact with water.

). Irrigate immediately with large quantity of water for at least 15 minutes. Call a physician if irritation develops. Remove to fresh air. Give artificial respiration if necessary. If breathing is difficult, give oxygen. Wash areas of contact with soap and water for at least 15 minutes. Call a physician if irritation develops. Dilute with water or milk. Do not induce vomiting. Call a physician if necessary.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing Media

Use any means suitable for extinguishing surrounding fire (water or water spray). Neutralize with soda ash or slaked lime.

5.2. Specific Hazards Arising from the Substance or Mixture

Not considered to be a fire or explosion hazard. May react with metals to release flammable Hydrogen gas.

Product Number: PAL10KH Page 3 of 16

5.3. Special Protective Equipment for Firefighters

Use protective clothing and breathing equipment appropriate for the surrounding fire.

SECTION 6: Accidental Release Measures

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

Wear protective gloves and eye protection.

6.2. Cleanup and Containment Methods and Materials

Cover the spill with Sodium Carbonate or a soda ash-slaked lime mixture (50:50). Mix and add water to form slurry. Decant the liquid to the drain with excess water. Treat the solid residue as normal refuse. Wash site with soda ash solution. Always dispose of in accordance with local regulations.

SECTION 7: Handling and Storage

7.1. Precautions for Safe Handling and Storage Conditions

Store in corrosive resistant container with a resistant inner liner. As with all chemicals, wash hands thoroughly after handling. Avoid contact with eyes and skin. Protect from freezing and physical damage.

Product Number: PAL10KH Page 4 of 16



Safety Data Sheet

SECTION 8: Exposure Controls / Personal Protection

8.1 Control Parameters

Chemical Name	Limit Type	Country	Exposure Limit	Information Source
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)
Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)

Product Number: PAL10KH Page 5 of 16



Safety Data Sheet

Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)
Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TWA	USA	15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)
Aluminum (7429-90-5)	TLV-TWA	USA	1 mg/m³ TWA (respirable particulate matter)	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)

Product Number: PAL10KH Page 6 of 16



Safety Data Sheet

Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Aluminum (7429-90-5)	TWA	USA	"15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction)" As Aluminum metal [7429-90-5]	U.S OSHA - Final PELs - Time Weighted Averages (TWAs)
Aluminum (7429-90-5)	TLV-TWA	USA	"1 mg/m³ TWA (respirable particulate matter)" As Aluminum [7429-90-5]	ACGIH - Threshold Limit Values - Time Weighted Averages (TLV-TWA)
Hydrochloric Acid (7647-01-0)	PEL-Ceiling	USA	"5 ppm Ceiling; 7 mg/m³ Ceiling" As Hydrogen chloride [7647-01-0]	U.S OSHA - Final PELs - Ceiling Limits
Hydrochloric Acid (7647-01-0)	TLV-Ceiling	USA	"2 ppm Ceiling" As Hydrogen chloride [7647-01-0]	ACGIH - Threshold Limit Values - Ceilings (TLV-C)
Hydrochloric Acid (7647-01-0)	TLV-Ceiling	USA	"2 ppm Ceiling" As Hydrogen chloride [7647-01-0]	ACGIH - Threshold Limit Values - Ceilings (TLV-C)
Hydrochloric Acid (7647-01-0)	PEL-Ceiling	USA	"5 ppm Ceiling; 7 mg/m³ Ceiling" As Hydrogen chloride [7647-01-0]	U.S OSHA - Final PELs - Ceiling Limits

Product Number: PAL10KH Page 7 of 16



Safety Data Sheet

Hydrochloric Acid (7647-01-0)	TLV-Ceiling	USA	"2 ppm Ceiling" As Hydrogen chloride	ACGIH - Threshold Limit Values - Ceilings (TLV-C)
			[7647-01-0]	
Hydrochloric Acid (7647-01-0)	PEL-Ceiling	USA	"5 ppm Ceiling; 7 mg/m ³	U.S OSHA - Final PELs - Ceiling
,	· ·		Ceiling" As Hydrogen	Limits
			chloride [7647-01-0]	
Hydrochloric Acid (7647-01-0)	TLV-Ceiling	USA	"2 ppm Ceiling" As	ACGIH - Threshold Limit Values -
	_		Hydrogen chloride	Ceilings (TLV-C)
			[7647-01-0]	
Hydrochloric Acid (7647-01-0)	PEL-Ceiling	USA	"5 ppm Ceiling; 7 mg/m ³	U.S OSHA - Final PELs - Ceiling
			Ceiling" As Hydrogen	Limits
			chloride [7647-01-0]	
Hydrochloric Acid (7647-01-0)	TLV-Ceiling	USA	2 ppm Ceiling	ACGIH - Threshold Limit Values -
				Ceilings (TLV-C)
Hydrochloric Acid (7647-01-0)	PEL-Ceiling	USA	5 ppm Ceiling; 7 mg/m ³	U.S OSHA - Final PELs - Ceiling
			Ceiling	Limits
Hydrochloric Acid (7647-01-0)	TLV-Ceiling	USA	"2 ppm Ceiling" As	ACGIH - Threshold Limit Values -
			Hydrogen chloride	Ceilings (TLV-C)
			[7647-01-0]	
Hydrochloric Acid (7647-01-0)	PEL-Ceiling	USA	"5 ppm Ceiling; 7 mg/m ³	U.S OSHA - Final PELs - Ceiling
			Ceiling" As Hydrogen	Limits
			chloride [7647-01-0]	
Hydrochloric Acid (7647-01-0)	TLV-Ceiling	USA	"2 ppm Ceiling" As	ACGIH - Threshold Limit Values -
			Hydrogen chloride	Ceilings (TLV-C)
			[7647-01-0]	
Hydrochloric Acid (7647-01-0)	PEL-Ceiling	USA	"5 ppm Ceiling; 7 mg/m ³	U.S OSHA - Final PELs - Ceiling
			Ceiling" As Hydrogen	Limits
			chloride [7647-01-0]	
Hydrochloric Acid (7647-01-0)	PEL-Ceiling	USA	"5 ppm Ceiling; 7 mg/m ³	U.S OSHA - Final PELs - Ceiling
			Ceiling" As Hydrogen	Limits
			chloride [7647-01-0]	
Hydrochloric Acid (7647-01-0)	TLV-Ceiling	USA	"2 ppm Ceiling" As	ACGIH - Threshold Limit Values -
			Hydrogen chloride	Ceilings (TLV-C)
			[7647-01-0]	

8.2. Exposure Controls

Engineering Controls: No specific controls are needed. Normal room ventilation is adequate.

Respiratory Protection: Normal room ventilation is adequate.

Skin Protection: Wear protective gloves and eye protection. Chemical resistant gloves. **Eye Protection:** Wear protective gloves and eye protection. Safety glasses or goggles.

Product Number: PAL10KH Page 8 of 16

8.3. Personal Protective Equipment

Wear protective gloves and eye protection. Normal room ventilation is adequate. Chemical resistant gloves. Safety glasses or goggles.

SECTION 9: Physical and Chemical Properties

9.1. Basic Physical and Chemical Properties

Appearance: Colorless liquid

Physical State: Liquid

Odor: Data not available.

Odor Threshold: Data not available.

pH: < 1

Melting/Freezing Point: Approximately 0°C

Initial Boiling Point/Range: Approximately 100°C - Approximately 100°C

Flash Point: Data not available.

Evaporation Rate: Data not available.

Flammability: Data not available.

Flammability/Explosive Limits: Data not available.

Vapor Pressure: Data not available.

Vapor Density: Data not available.

Relative Density: 1.03

Solubility: Miscible

Partition Coefficient: Data not available.

Auto-Ignition Temperature: Data not available.

Decomposition Temperature: Data not available.

Viscosity: Data not available.

Explosive Properties: Data not available.

Oxidizing Properties: Data not available.

SECTION 10: Stability and Reactivity

10.1. Reactivity and Chemical Stability

Stable under normal conditions of use and storage.

10.2. Possibility of Hazardous Reactions

Data not available.

Product Number: PAL10KH Page 9 of 16

10.3. Conditions to Avoid and Incompatible Materials

Keep only in original container. Sodium Oxide, Ethylene Oxide, Nitromethane, most metals, Alkalis, active metals, Cyanides, Sulfides, Sulfites, Metal Oxides, Formaldehyde. Reacts with most metals to produce Hydrogen gas which may explode.

10.4. Hazardous Decomposition Products

Will not occur.

SECTION 11: Toxicological Information

11.1. Information on Toxicological Effects

Acute Toxicity - Oral Exposure:

Not applicable.

Acute Toxicity - Dermal Exposure:

Not applicable.

Acute Toxicity - Inhalation Exposure:

Not applicable.

Acute Toxicity - Other Information:

LD50, Oral, Rabbit (Hydrochloric Acid) 900 mg/kg; Details of toxic effects not reported other than lethal dose value. LCLo, inhalation, human: 3000 ppm/5 minutes: No toxic effects noted.

Skin Corrosion and Irritation:

Causes severe skin burns and eye damage. Do not breathe fumes, mist, vapors, or spray. Wash arms, hands and face thoroughly after handling. Wear protective gloves and eye protection. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. Specific treatment (Wash areas of contact with water.

). IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents in accordance with local, state, federal and international regulations.

Serious Eye Damage and Irritation:

Causes serious eye damage. Wear protective gloves and eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

Respiratory Sensitization:

Not applicable.

Skin Sensitization:

Not applicable.

Germ Cell Mutagenicity:

Not applicable.

Carcinogenicity:

Not applicable.

Reproductive Toxicity:

Not applicable.

Product Number: PAL10KH Page 10 of 16

Specific Target Organ Toxicity from Single Exposure:

Not applicable.

Specific Target Organ Toxicity from Repeated Exposure:

Not applicable.

Aspiration Hazard:

Not applicable.

Additional Toxicology Information:

Data not available.

SECTION 12: Ecological Information

12.1. Ecotoxicity

Not applicable.

12.2. Persistence and Degradability

Data not available.

12.3. Bioaccumulative Potential

Data not available.

12.4. Mobility in Soil

Data not available.

12.5. Other Adverse Ecological Effects

Data not available.

SECTION 13: Disposal Considerations

13.1. Waste Treatment Methods

Data not available.

Product Number: PAL10KH Page 11 of 16



SECTION 14: Transportation Information

14.1. Transportation by Land-Department of Transportation (DOT, United States of America)

Sizes: 100 mL, 500 mL

UN Number: UN1789

Proper Shipping Name: Hydrochloric Acid Solution

Hazard Class: 8

Packing Group: |||

Hazard Label(s):



14.2. Transportation by Air - International Air Transport Association (IATA)

Sizes: 100 mL, 500 mL

UN Number: UN1789

Proper Shipping Name: Hydrochloric Acid Solution

Hazard Class: 8

Packing Group: |||

Hazard Label(s):



14.3 Transportation of Dangerous Goods (TDG, Canada)

Sizes: 100 mL, 500 mL

UN Number: UN1789

Proper Shipping Name: HYDROCHLORIC ACID SOLUTION

Hazard Class: 8

Packing Group: |||

Hazard Label(s):



Product Number: PAL10KH Page 12 of 16

SECTION 15: Regulatory Information

15.1. Occupational Safety and Health Administration (OSHA) Hazards

Not listed.

15.2. Superfund Amendments and Reauthorization Act (SARA) 302 Extremely Hazardous Substances

Hydrochloric Acid (CAS # 7647-01-0): "500 lb TPQ (gas only)" As Hydrogen chloride [7647-01-0]

Hydrochloric Acid (CAS # 7647-01-0): "5000 lb EPCRA RQ (gas only)" As Hydrogen chloride [7647-01-0]

Hydrochloric Acid (CAS # 7647-01-0): 500 lb TPQ (gas only)

Hydrochloric Acid (CAS # 7647-01-0): 5000 lb EPCRA RQ (gas only)

15.3. Superfund Amendments and Reauthorization Act (SARA) 311/312 Hazardous Chemicals

Hydrochloric Acid (CAS # 7647-01-0): "5000 lb final RQ; 2270 kg final RQ" As Hydrochloric acid [7647-01-0]

Hydrochloric Acid (CAS # 7647-01-0): 5000 lb final RQ; 2270 kg final RQ

15.4. Superfund Amendments and Reauthorization Act (SARA) 313 Toxic Release Inventory (TRI)

Aluminum (CAS # 7429-90-5): "1.0 % de minimis concentration (dust or fume only)" As Aluminum [7429-90-5]

Aluminum (CAS # 7429-90-5): 1.0 % de minimis concentration (dust or fume only)

Hydrochloric Acid (CAS # 7647-01-0): "1.0 % de minimis concentration (acid aerosols including mists, vapors, gas, fog, and other airborne forms of an particle size)" As Hydrochloric acid [7647-01-0]

Hydrochloric Acid (CAS # 7647-01-0): 1.0 % de minimis concentration (acid aerosols including mists, vapors, gas, fog, and other airborne forms of any particle size)

15.5. Massachusetts Right-to-Know Substance List

Aluminum (CAS # 7429-90-5): "Present" As Aluminum [7429-90-5]

Aluminum (CAS # 7429-90-5): Present

Hydrochloric Acid (CAS # 7647-01-0): "Extraordinarily hazardous" As Hydrochloric acid [7647-01-0]

Hydrochloric Acid (CAS # 7647-01-0): Extraordinarily hazardous

15.6. Pennsylvania Right-to-Know Hazardous Substances

Aluminum (CAS # 7429-90-5): "Environmental hazard; Present (dust)" As Aluminum [7429-90-5]

Aluminum (CAS # 7429-90-5): "Present" As Aluminum [7429-90-5]

Aluminum (CAS # 7429-90-5): Environmental hazard; Present (dust)

Aluminum (CAS # 7429-90-5): Present

Hydrochloric Acid (CAS # 7647-01-0): "Environmental hazard" As Hydrochloric acid [7647-01-0]

Hydrochloric Acid (CAS # 7647-01-0): "Present" As Hydrochloric acid [7647-01-0]

Hydrochloric Acid (CAS # 7647-01-0): Environmental hazard

Hydrochloric Acid (CAS # 7647-01-0): Present

Water (CAS # 7732-18-5): "Present" As Ethyl alcohol and water [RR-00802-6]

Water (CAS # 7732-18-5): Present

Product Number: PAL10KH Page 13 of 16

15.7. New Jersey Worker and Community Right-to-Know Components

Aluminum (CAS # 7429-90-5): "flammable - third degree" As Aluminum [7429-90-5]

Aluminum (CAS # 7429-90-5): "SN 0054 500 lb TPQ (dust or fume)" As Aluminum [7429-90-5]

Aluminum (CAS # 7429-90-5): "sn 0054" As Aluminum [7429-90-5]

Aluminum (CAS # 7429-90-5): flammable - third degree

Aluminum (CAS # 7429-90-5): sn 0054

Aluminum (CAS # 7429-90-5): SN 0054 500 lb TPQ (dust or fume)

Hydrochloric Acid (CAS # 7647-01-0): "corrosive" As Hydrogen chloride [7647-01-0]

Hydrochloric Acid (CAS # 7647-01-0): "SN 1012 500 lb TPQ; SN 2909 500 lb TPQ (gas only)" As Hydrogen chloride [7647-01-0]

Hydrochloric Acid (CAS # 7647-01-0): "sn 1012" As Hydrogen chloride [7647-01-0]

Hydrochloric Acid (CAS # 7647-01-0): corrosive Hydrochloric Acid (CAS # 7647-01-0): sn 1012

Hydrochloric Acid (CAS # 7647-01-0): SN 1012 500 lb TPQ; SN 2909 500 lb TPQ (gas only)

15.8. California Proposition 65

Not listed.

15.9. Canada Domestic Substances List / Non-Domestic Substances List (DSL/NDSL)

Aluminum (CAS # 7429-90-5): "Present" As Aluminum [7429-90-5] (DSL)

Aluminum (CAS # 7429-90-5): Present (DSL)

Hydrochloric Acid (CAS # 7647-01-0): "Present" As Hydrogen chloride [7647-01-0] (DSL)

Hydrochloric Acid (CAS # 7647-01-0): Present (DSL)

Water (CAS # 7732-18-5): "Present" As Water [7732-18-5] (DSL)

Water (CAS # 7732-18-5): Present (DSL)

15.10. United States of America Toxic Substances Control Act (TSCA) List

All components of this solution are listed as active on the TSCA Inventory or are mixtures (hydrates) of active items listed on the TSCA Inventory.

Aluminum (CAS # 7429-90-5): "Present (ACTIVE)" As Aluminum [7429-90-5]

Aluminum (CAS # 7429-90-5): Present (ACTIVE)

Hydrochloric Acid (CAS # 7647-01-0): "Present (ACTIVE)" As Hydrochloric acid [7647-01-0]

Hydrochloric Acid (CAS # 7647-01-0): Present (ACTIVE)

Water (CAS # 7732-18-5): "Present (ACTIVE)" As Water [7732-18-5]

Water (CAS # 7732-18-5): Present (ACTIVE)

15.11. European Inventory of Existing Commercial Chemical Substances (EINECS), European List of Notified Chemical Substances (ELINCS), and No Longer Polymers (NLP)

Aluminum (CAS # 7429-90-5): "231-072-3" As Aluminium [7429-90-5]

Aluminum (CAS # 7429-90-5): 231-072-3

Hydrochloric Acid (CAS # 7647-01-0): "231-595-7" As Hydrogen chloride [7647-01-0]

Hydrochloric Acid (CAS # 7647-01-0): 231-595-7

Water (CAS # 7732-18-5): "231-791-2" As Water [7732-18-5]

Water (CAS # 7732-18-5): 231-791-2

Product Number: PAL10KH Page 14 of 16



SECTION 16: Other Information

16.1. Full Text of Hazard Statements and Precautionary Statements

May be corrosive to metals. Causes severe skin burns and eye damage.

Keep only in original container. Do not breathe fumes, mist, vapors, or spray. Wash arms, hands and face thoroughly after handling. Wear protective gloves and eye protection.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician. Specific treatment (Wash areas of contact with water.

). Wash contaminated clothing before reuse. Absorb spillage to prevent material damage.

Store locked up. Store in corrosive resistant container with a resistant inner liner.

Dispose of contents in accordance with local, state, federal and international regulations.

16.2. Miscellaneous Hazard Classes

Canadian Carcinogenicity Hazard Class: Not Applicable.


Physical Hazards Not Otherwise Classified (PHNOC): Not Applicable.

Health Hazards Not Otherwise Classified (HHNOC): Not Applicable.

Biohazardous Infectious Materials Hazard Class: Not Applicable.

16.3. National Fire Protection Association (NFPA) Rating

Health: 2
Flammability: 0
Reactivity: 0
Special Hazard:



16.4. Document Revision

Last Revision Date: 2025-02-02

Product Number: PAL10KH Page 15 of 16

DISCLAIMER

When handled properly by qualified personnel, the product described herein does not present a significant health or safety hazard. Alteration of its characteristics by concentration, evaporation, addition of other substances, or other means may present hazards not specifically addressed herein and which must be evaluated by the user. The information furnished herein is believed to be accurate and represents the best data currently available to us. No warranty, expressed or implied, is made and RICCA CHEMICAL COMPANY assumes no legal responsibility or liability whatsoever resulting from its use.

Product Number: PAL10KH Page 16 of 16