

Product Specification

Sodium Hydroxide, 6.00 Normal

Lot Number: SAMPLE

Product Number: 7466

Manufacture Date: N/A

Expiration Date: N/A

Name	CAS#	Grade
Water	7732-18-5	ACS/ASTM/USP/EP
Sodium Hydroxide	1310-73-2	Reagent

Test	Specification	Result	NIST SRM#
Appearance	Colorless liquid	N/A	
Assay (vs. Sulfuric Acid/Phenolphthalein)	5.995-6.005 N at 20°C	N/A	723

Specification	Reference
Sodium Hydroxide Solution (240 g/L)	ASTM (D 1426 A)
Sodium Hydroxide Solution, 6 N	APHA (4500-S2- B)
Sodium Hydroxide Solution, 6 N	APHA (4500-S2- C)
Sodium Hydroxide, 6 N	APHA (4500-P B)
Sodium Hydroxide, 6 N	APHA (4500-Norg C)
Sodium hydroxide, 6 N	APHA (4500-CIO2 C)
Sodium Hydroxide, 6 N	APHA (4500-NH3 B)
Sodium Hydroxide, 6 N	APHA (4500-Norg B)
Sodium Hydroxide, 6 N	APHA (3500-K C)
Sodium Hydroxide, 6 N	APHA (3500-Ni D)
Sodium Hydroxide, 6 N	APHA (3500-Cd D)
Sodium Hydroxide (6 N)	EPA (SW-846) (9030B)
Sodium Hydroxide (6 N)	EPA (SW-846) (9215)
Sodium Hydroxide, 6 N	EPA (SW-846) (9315)
Sodium Hydroxide, 6 N	EPA (430.1)
Sodium Hydroxide, 6 N	EPA (430.2)
Sodium Hydroxide Solution, 6 N	EPA (353.3)
Sodium Hydroxide (6 M)	ASTM (D 4922)
Sodium Hydroxide Solution (240 g/L)	ASTM (D 1426 X1)

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
7466-1	4 L natural poly	24 months
7466-16	500 mL natural poly	24 months
7466-2.5	10 L Cubitainer®	24 months
7466-32	1 L natural poly	24 months
7466-5	20 L Cubitainer®	24 months
7466-55	55 gal poly drum	24 months
7466-5HP	20 L Ropak™	24 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.