

Product Specification

Mixed ICP Standard

50 ppm Al, B, Ba, Ca, Fe, K, Li, Mg, Mn, Na, Pb, Sr, Zn

Lot Number: SAMPLE

Product Number: RPMX100N

Manufacture Date: N/A

Expiration Date: N/A

Matrix: 5% Nitric Acid

Name	CAS#	Grade
Water	7732-18-5	ACS/ASTM/USP/EP
Nitric Acid	7697-37-2	Trace Metals
Ammonium Hydroxide	1336-21-6	Trace Metals

Test	Specification	Result
Appearance	Colorless liquid	N/A

Analyte	Analysis (ppm)	Solute	CAS#	Grade	NIST SRM#
Aluminum (Al)	49.5-50.5 ppm	Aluminum Nitrate Nonahydrate	7784-27-2	High Purity	3101
Boron (B)	49.5-50.5 ppm	Boric Acid	10043-35-3	High Purity	3107
Lithium (Li)	49.5-50.5 ppm	Lithium Carbonate, 6Li ₂ CO ₃	554-13-2	High Purity	3129
Calcium (Ca)	49.5-50.5 ppm	Calcium Carbonate	471-34-1	High Purity	3109
Strontium (Sr)	49.5-50.5 ppm	Strontium Nitrate	10042-76-9	High Purity	3153
Sodium (Na)	49.5-50.5 ppm	Sodium Carbonate	497-19-8	High Purity	3152
Barium (Ba)	49.5-50.5 ppm	Barium Nitrate	10022-31-8	High Purity	3104
Potassium (K)	49.5-50.5 ppm	Potassium Carbonate	584-08-7	High Purity	3141
Zinc (Zn)	49.5-50.5 ppm	Zinc	7440-66-6	High Purity	3168
Manganese (Mn)	49.5-50.5 ppm	Manganese	7439-96-5	High Purity	3132
Magnesium (Mg)	49.5-50.5 ppm	Magnesium	7439-95-4	High Purity	3131
Lead (Pb)	49.5-50.5 ppm	Lead	7439-92-1	High Purity	3128
Iron (Fe)	49.5-50.5 ppm	Iron	7439-89-6	High Purity	3126

This standard is guaranteed to be stable and accurate provided the product is kept tightly capped and stored under normal laboratory conditions. Balances are calibrated using NIST traceable weights whose verification of maintenance and recalibration is documented per in-house Standard Operating Procedures. Class A glassware is also calibrated and routinely rechecked per in-house Standard Operating Procedures. Trace metal analyzed acids and Trace Metals Analyzed Water are used in the manufacture of this product. Triple cleaned containers are used in the manufacture of this product.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
RPMX100N-1N	1 L natural poly	12 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

This test report shall not be reproduced, except in full, without the written approval of Ricca Chemical Company.